

RAPPLON® QSP 60 Plus

6 adjustable heat settings for a wide variety of belt types and styles



Get rid of the yellow cabinet!
No toxic chemicals or adhesives needed with RAPPLON® Quick-Splice products!

Ammeraal Beltech's Quick-Splice technology eliminates hazardous exposures associated with belt splicing adhesives.

Onsite installation of your own belts is now possible using Quick-Splice tools. Eliminate the delays and liabilities associated with contract installers, by doing it yourself.

Quick-Splice tools from Ammeraal Beltech reduce installation time to just a few minutes. It's easy! We show you how!



QSP 60 Plus pliers w/stand
Items 615340/62355



CP 60 Cooling pliers
Item 62291




Clamps - red (pair)
Item 62351



Clamps - metal (pair)
Item 62352



Digital timer
Item 62350



Guide rail
Various widths available



Cutter
Item 62312



HFT 50/100 Manual punch tool
Item 62356

Select your specific Quick-Splice Pliers



QSP 60 Plus press, set items and splicing rails

Item #	Description	Voltage	Plug
Complete press kit (without guide rails)			
62380	QSP 60 Plus Standard	110 V	US Plug
62387	QSP 60 Plus/HFT 50 Deluxe*	110 V	US Plug
Set items			
615340	QSP 60 Plus heating pliers	110 V	US Plug
62355	QSP press stand		
62291	CP 60 Cooling pliers		
62351	Clamps "red" (pair)		
62352	Metal clamps (pair)		
62350	Digital timer		
62353	Carry and storage case		
62356	*HFT 50/100 Cutter		

All rails sold separately.

Splicing rails

Rails available for widths from 5-60mm and .5-6mm thickness range. Custom splice rails are possible up to 9" wide.

QSP 60 Plus available as a Standard or Deluxe kit



The QSP 60 Plus Standard Kit comes equipped with one each QSP 60 Plus press, CP 60 Cooling pliers, press stand, digital timer, butt end cutting tool and two pairs of securing clamps complete in a convenient carrying case.

* The Deluxe kit adds the HFT 50/100 Finger Cutting Tool.

Available finger punching equipment



MFT 40



MFT 130 and MFT 250



HFT 50/100

Guide rails available for widths up to 9"



Contact factory for press selection if belt width is greater than 60mm.

QSP 60 Plus Specifications

Dimensions - L x W x H (mm):	260 x 72 x 96
Weight (kg):	1
Heated surface area (mm):	60 x 65
Maximum belt width (mm):	60
Maximum belt joint length (mm):	50
Maximum belt thickness (mm):	6
Temperature settings (°C):	110/130/160/170/180/185/190/195/200/205
Preheating time:	4-6 minutes
Voltage (V):	110 standard/230 available

Headquarters:

Ammeraal Beltech Inc.
7501 N. St. Louis Avenue
Skokie, IL 60076-4000

Phone 847 673 6720
Fax 847 673 6373
Toll free 800 323 4170
info@ammeraalbeltechusa.com
www.Ammeraal-Beltechusa.com

Marietta, GA
Toll free 800 533 3765

Grand Prairie, TX
Toll free 800 533 3765

Jefferson, PA
Toll free 800 533 3765

Reading, PA
Toll free 800 533 3765

Wyoming, MI
Toll free 866 791 0162

Sante Fe Springs, CA
Toll free 866 778 9017

Warwick, RI
Toll free 800 533 3765

Eugene, OR
Toll free 866 778 9017

Kent, WA
Toll free 866 778 9017

Ontario, Canada
Toll free 800 455 3337

Québec, Canada
Toll free 800 455 3337

