

RAPPLON® Flat Belts Sales Program



RAPPLON® QuickSplice Flat belts

- Process belts
- Elastic process belts
- Drive belts and Tangential drive belts

RAPPLON® Classic Flat belts

- Process belts
- Drive belts with elastomer cover
- Drive belts with leather cover
- Tangential drive belts
- Spindle tapes
- Drive belts with grooved elastomer cover

RAPPLON® QuickSplice Flat Belts

| Belt type | Article Number | Belt thickness [mm] | Belt weight [kg/m ²] | Min. pulley diameter [mm, 20°C] | Belt factor at 1% elongation [N/mm] | Antistatic [AS] | Recommended elongation [%] | Thermal application range [°C] | Cover running side [Material, colour, surface structure] | Cover back side [Material, colour, surface structure] | Tension member [Material] |
|------------------------------|----------------|---------------------|----------------------------------|---------------------------------|-------------------------------------|-----------------|----------------------------|--------------------------------|----------------------------------------------------------|-------------------------------------------------------|---------------------------|
| Process belts | | | | | | | | | | | |
| TT P2 Q | 54601 | 1.10 | 1.00 | 10 | 2 | yes | 1.0 - 2.0 | -20 / +60 | Polyamide fabric, green | Polyamide fabric, black | Polyamide fabric |
| TT P8 Q | 54602 | 1.80 | 1.60 | 25 | 8 | yes | 1.0 - 2.0 | -20 / +60 | Polyamide fabric, grey | Polyamide fabric, grey | Polyamide fabric |
| TT E5 Q | 54599 | 1.10 | 1.10 | 25 | 5 | yes | 0.5 - 2.1 | -20 / +60 | Polyester fabric, grey | Polyester fabric, black | Polyester fabric |
| TT E6 Q | 54600 | 1.75 | 1.710 | 25 | 6 | yes | 0.5 - 2.1 | -20 / +60 | Mixed fabric, grey | Mixed fabric, grey | Mixed fabric |
| TT E9 Q | 54598 | 1.85 | 1.90 | 25 | 9 | yes | 0.5 - 2.1 | -20 / +60 | Mixed fabric, grey | Mixed fabric, grey | Mixed fabric |
| GG P2 FFQ | 54582 | 1.50 | 1.60 | 25 | 2 | yes | 1.0 - 2.0 | -20 / +60 | XNBR elastomer, green, fine | XNBR elastomer, green, fine | Polyamide fabric |
| GG E5 FFQ | 54607 | 1.40 | 1.50 | 25 | 5 | yes | 0.3 - 2.1 | -20 / +60 | XNBR elastomer, black, fine | XNBR elastomer, green, fine | Polyester fabric |
| TG E4 RQ | 54624 | 1.25 | 1.25 | 15 | 4 | yes | 0.3 - 2.1 | -20 / +60 | Polyester fabric, green | NBR elastomer, green, rough | Polyester fabric |
| TG E4 FQ | 54628 | 1.25 | 1.25 | 15 | 4 | yes | 0.3 - 2.1 | -20 / +60 | Polyester fabric, green | NBR elastomer, green, fine | Polyester fabric |
| TU E4 RQ | 54603 | 0.90 | 1.05 | 15 | 4 | yes | 0.3 - 2.1 | -20 / +60 | Polyester fabric | Polyurethane, black, rough | Polyester fabric |
| PG E5 SFQ | 54630 | 1.20 | 1.20 | 20 | 5 | yes | 0.3 - 2.1 | -20 / +60 | TPE, black, smooth | XNBR elastomer, green, fine | Polyester fabric |
| PG E8 SFQ | 54631 | 1.85 | 1.90 | 30 | 8 | yes | 0.3 - 2.1 | -20 / +60 | TPE, black, smooth | XNBR elastomer, green, fine | Polyester fabric |
| UU E15.30 RRQ | 54538 | 3.00 | 3.30 | 30 | 15 | yes | 0.3 - 2.1 | -20 / +60 | Polyurethane, green, rough | Polyurethane, green, rough | Polyester fabric |
| Elastic process belts | | | | | | | | | | | |
| UU 8E RSQ white | 54543 | 0.80 | 0.95 | Knife edge | 0.8* | no | 3.0 - 6.0 | -20 / +60 | Polyurethane, white, rough | Polyurethane, white, smooth | Polyurethane |
| UU 8E RFQ | 54544 | 0.80 | 0.95 | 20 | 0.5* | yes | 3.0 - 6.0 | -20 / +60 | Polyurethane, black, rough | Polyurethane, blue, fine | Polyurethane |
| UU 10E RFQ | 54545 | 1.10 | 1.20 | 20 | 0.6* | yes | 3.0 - 6.0 | -20 / +60 | Polyurethane, black, rough | Polyurethane, blue, fine | Polyurethane |
| GG 2E RRQ | 54262 | 1.50 | 1.40 | 15 | 0.8* | yes | 4.0 - 8.0 | -20 / +60 | XNBR elastomer, black, rough | XNBR elastomer, green, rough | TPE |
| GG 4E RFQ | 54263 | 1.50 | 1.40 | 15 | 2.2* | yes | 4.0 - 8.0 | -20 / +60 | XNBR elastomer, black, rough | XNBR elastomer, green, fine | TPE |
| GG 6E RFQ | 54608 | 1.70 | 1.65 | 15 | 2.7* | yes | 4.0 - 8.0 | -20 / +60 | XNBR elastomer, black, rough | XNBR elastomer, green, fine | TPE |
| GV 4E RQ | 54547 | 1.60 | 1.50 | 15 | 0.5 | yes | 0.3 - 2.1 | -20 / +60 | XNBR elastomer, black, rough | Fleece, grey | TPE |

* Belt factor at 6%

Material
TPE > Thermoplastic elastomer

RAPPLON® QuickSplice Flat Belts

| Belt type | Article Number | Belt thickness [mm] | Belt weight [kg/m ²] | Min. pulley diameter [mm, 20°C] | Belt factor at 1% elongation [N/mm] | Antistatic [AS] | Recommended elongation [%] | Thermal application range [°C] | Cover running side [Material, colour, surface structure] | Cover back side [Material, colour, surface structure] | Tension member [Material] |
|-----------------------------------------------|----------------|---------------------|----------------------------------|---------------------------------|-------------------------------------|-----------------|----------------------------|--------------------------------|----------------------------------------------------------|-------------------------------------------------------|---------------------------|
| Drive belts and Tangential drive belts | | | | | | | | | | | |
| GG E8.20 RRQ | 54614 | 2.00 | 2.00 | 25 | 8 | yes | 0.3 - 2.1 | -20 / +60 | XNBR elastomer, black, rough | XNBR elastomer, blue, rough | Polyester fabric |
| GG E15.20 RRQ | 54626 | 2.00 | 2.20 | 25 | 15 | yes | 0.3 - 2.1 | -20 / +60 | XNBR elastomer, green, rough | XNBR elastomer, blue, rough | Polyester fabric |
| GG E15.25 RRQ | 54618 | 2.50 | 2.50 | 30 | 15 | yes | 0.3 - 2.1 | -20 / +60 | XNBR elastomer, green, rough | XNBR elastomer, blue, rough | Polyester fabric |
| GG E15.30 RRQ | 54609 | 3.00 | 3.30 | 30 | 15 | yes | 0.3 - 2.1 | -20 / +60 | XNBR elastomer, green, rough | XNBR elastomer, blue, rough | Polyester fabric |
| GG A22 RRQ | 54612 | 2.00 | 2.00 | 25 | 22 | yes | 0.3 - 0.8 | -20 / +60 | XNBR elastomer, green, rough | XNBR elastomer, blue, rough | Aramide fabric |

RAPPLON® QuickSplice Tools

Finger cutting equipment



HFT 30/100 & HFT 50/100



MFT 40



MFT 130 & MFT 250



MFT 400



AFT 60

Heating pliers



QSP 60



QSP 60 plus



QSP 60LF plus



QSP 105 plus



QSP 160 plus

RAPPLON® Classic Flat Belts

| Belt type | Article Number | Belt thickness [mm] | Belt weight [kg/m ²] | Min. pulley diameter [mm, 20°C] | Belt factor at 1% elongation [N/mm] | Antistatic [AS] | Recommended elongation [%] | Thermal application range [°C] | Cover running side [Material, colour, surface structure] | Cover back side [Material, colour, surface structure] | Tension member [Material] |
|----------------------|----------------|---------------------|----------------------------------|---------------------------------|-------------------------------------|-----------------|----------------------------|--------------------------------|----------------------------------------------------------|-------------------------------------------------------|---------------------------|
| Process belts | | | | | | | | | | | |
| FF 04 | 54089 | 1.40 | 1.60 | 50 | 4 | yes | 2.0 - 3.0 | -10 / +80 | Polyamide foil, blue, smooth | Polyamide foil, blue, smooth | Polyamide foil |
| TT 02 | 54270 | 1.00 | 0.85 | 10 | 2 | yes | 2.0 - 3.0 | -20 / +100 | Polyamide fabric, blue | Polyamide fabric, blue | Polyamide foil |
| TT 04 | 54054 | 1.20 | 1.15 | 20 | 4 | yes | 2.0 - 3.0 | -20 / +100 | Polyamide fabric, blue | Polyamide fabric, blue | Polyamide foil |
| TT 04 AS | 54251 | 1.20 | 1.10 | 20 | 4 | yes | 2.0 - 3.0 | -20 / +100 | Polyamide fabric, black | Polyamide fabric, black | Polyamide foil |
| TT 09 AS | 54250 | 1.65 | 1.65 | 60 | 9 | yes | 2.0 - 3.0 | -20 / +100 | Polyamide fabric, black | Polyamide fabric, black | Polyamide foil |
| GG 02 FF | 54264 | 1.50 | 1.65 | 10 | 2 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, blue, fine | XNBR elastomer, blue, fine | Polyamide foil |
| GG 02 RE | 54009 | 1.10 | 1.20 | 10 | 2 | yes | 2.0 - 3.0 | -20 / +100 | NBR elastomer, blue, rough | NBR elastomer, blue, rough | Polyamide foil |
| GG 04 RE | 54010 | 1.30 | 1.50 | 20 | 4 | yes | 2.0 - 3.0 | -20 / +100 | NBR elastomer, blue, rough | NBR elastomer, blue, rough | Polyamide foil |
| GG 04/R10 | 54273 | 2.90 | 3.10 | 30 | 4 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, green, rough | XNBR elastomer, green, rough | Polyamide foil |
| GG 06/R10 | 54274 | 3.00 | 3.30 | 30 | 6 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, green, rough | XNBR elastomer, green, rough | Polyamide foil |
| GG 06/R15 | 54145 | 4.00 | 4.40 | 40 | 6 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, green, rough | XNBR elastomer, green, rough | Polyamide foil |
| GG 06/R20 | 54275 | 5.00 | 5.50 | 50 | 6 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, green, rough | XNBR elastomer, green, rough | Polyamide foil |
| GG 06/R25 | 54276 | 6.00 | 6.80 | 60 | 6 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, green, rough | XNBR elastomer, green, rough | Polyamide foil |
| GG 09/R10 | 54133 | 3.10 | 3.50 | 80 | 9 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, blue, rough | XNBR elastomer, blue, rough | Polyamide foil |
| GG 12/R25 | 54419 | 6.80 | 7.60 | 100 | 12 | yes | 2.0 - 3.0 | -20 / +100 | NBR elastomer, blue, rough | NBR elastomer, blue, rough | Polyamide foil |
| GG 18/R15 | 54141 | 5.30 | 6.10 | 200 | 18 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, blue, rough | XNBR elastomer, blue, rough | Polyamide foil |
| GT 09 F | 54166 | 1.90 | 2.10 | 60 | 9 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, blue, fine | Polyamide fabric, blue | Polyamide foil |

RAPPLON® Classic Flat Belts

| Belt type | Article Number | Belt thickness [mm] | Belt weight [kg/m ²] | Min. pulley diameter [mm, 20°C] | Belt factor at 1% elongation [N/mm] | Antistatic [AS] | Recommended elongation [%] | Thermal application range [°C] | Cover running side [Material, colour, surface structure] | Cover back side [Material, colour, surface structure] | Tension member [Material] |
|---------------------------|----------------|---------------------|----------------------------------|---------------------------------|-------------------------------------|-----------------|----------------------------|--------------------------------|----------------------------------------------------------|-------------------------------------------------------|---------------------------|
| Process belts | | | | | | | | | | | |
| TG 04 | 54261 | 1.40 | 1.40 | 20 | 4 | yes | 2.0 - 3.0 | -20 / +100 | Polyamide fabric, green | XNBR elastomer, green, rough | Polyamide foil |
| TG 20 | 54032 | 2.00 | 2.20 | 25 | 4 | yes | 2.0 - 3.0 | -20 / +100 | Polyamide fabric, blue | NBR elastomer, blue, rough | Polyamide foil |
| TG 30 | 54034 | 2.80 | 3.10 | 50 | 6 | yes | 2.0 - 3.0 | -20 / +100 | Polyamide fabric, blue | NBR elastomer, blue, rough | Polyamide foil |
| TG 40 | 54035 | 3.80 | 4.20 | 60 | 6 | yes | 2.0 - 3.0 | -20 / +100 | Polyamide fabric, blue | NBR elastomer, blue, rough | Polyamide foil |
| TG 60 | 54036 | 5.80 | 6.80 | 80 | 9 | yes | 2.0 - 3.0 | -20 / +100 | Polyamide fabric, blue | NBR elastomer, blue, rough | Polyamide foil |
| PTG 12 | 54525 | 1.25 | 1.20 | 25 | 3 | yes | 0.2 - 0.6 | -20 / +100 | Polyamide fabric, black | XNBR elastomer, green, fine | Polyamide fabric |
| PTG 20 | 54265 | 2.00 | 2.00 | 25 | 3.8 | yes | 0.2 - 0.6 | -20 / +100 | Polyamide fabric, black | NBR elastomer, green, rough | Polyamide fabric |
| PTG 30 | 54266 | 3.00 | 3.00 | 50 | 7 | yes | 0.2 - 0.6 | -20 / +100 | Polyamide fabric, black | NBR elastomer, green, rough | Polyamide fabric |
| PTG 40 | 54267 | 4.10 | 4.30 | 60 | 7 | yes | 0.2 - 0.6 | -20 / +100 | Polyamide fabric, black | NBR elastomer, green, rough | Polyamide fabric |
| PTG 60 | 54268 | 6.00 | 6.50 | 100 | 7 | yes | 0.2 - 0.6 | -20 / +100 | Polyamide fabric, black | NBR elastomer, green, rough | Polyamide fabric |
| ETG 10.18 white | 55145 | 1.70 | 1.90 | 60 | 10 | no | 0.2 - 0.6 | -20 / +100 | Polyester fabric, natural | NBR elastomer, white, smooth | Polyester fabric |
| ETG 10.18 P5 white | 55141 | 2.00 | 1.90 | 60 | 10 | no | 0.2 - 0.6 | -20 / +100 | Polyester fabric, natural | NBR elastomer, white, P5 | Polyester fabric |
| ETG 12.65 NR red | 56420 | 6.50 | 6.80 | 80 | 12 | yes | 0.2 - 0.6 | -10 / +70 | Polyester fabric, black | Natural rubber, red, smooth | Polyester fabric |
| ETG 18.20 P5 green | 57239 | 2.00 | 1.80 | 60 | 18 | yes | 0.2 - 0.6 | -20 / +100 | Polyester fabric, natural | NBR elastomer, green, P5 | Polyester fabric |

Surface structure

P5 > Fabric structure



RAPPLON® Classic Flat Belts

| Belt type | Article Number | Belt thickness [mm] | Belt weight [kg/m ²] | Min. pulley diameter [mm, 20°C] | Belt factor at 1% elongation [N/mm] | Antistatic [AS] | Recommended elongation [%] | Thermal application range [°C] | Cover running side [Material, colour, surface structure] | Cover back side [Material, colour, surface structure] | Tension member [Material] |
|-----------------------------------------|----------------|---------------------|----------------------------------|---------------------------------|-------------------------------------|-----------------|----------------------------|--------------------------------|----------------------------------------------------------|-------------------------------------------------------|---------------------------|
| Drive belts with elastomer cover | | | | | | | | | | | |
| GT 02 | 54001 | 1.10 | 1.00 | 10 | 2 | yes | 2.0 - 3.0 | -20 / +100 | NBR elastomer, blue, rough | Polyamide fabric, blue | Polyamide foil |
| GT 04 | 54002 | 1.30 | 1.30 | 20 | 4 | yes | 2.0 - 3.0 | -20 / +100 | NBR elastomer, blue, rough | Polyamide fabric, blue | Polyamide foil |
| GT 06 | 54003 | 1.50 | 1.50 | 40 | 6 | yes | 2.0 - 3.0 | -20 / +100 | NBR elastomer, blue, rough | Polyamide fabric, blue | Polyamide foil |
| GT 15 | 54006 | 2.70 | 2.90 | 120 | 15 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, blue, rough | Polyamide fabric, blue | Polyamide foil |
| GT 27 | 54008 | 4.00 | 4.40 | 300 | 27 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, blue, rough | Polyamide fabric, blue | Polyamide foil |
| GG 06/R | 54100 | 2.00 | 2.20 | 40 | 6 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, blue, rough | XNBR elastomer, blue, rough | Polyamide foil |
| GG 09/R | 54098 | 2.30 | 2.50 | 60 | 9 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, blue, rough | XNBR elastomer, blue, rough | Polyamide foil |
| Drive belts with leather cover | | | | | | | | | | | |
| LT 06 | 54045 | 2.60 | 2.50 | 50 | 6 | yes | 2.0 - 3.0 | -20 / +80 | Chrome leather, grey, ground | Polyamide fabric, black | Polyamide foil |
| LT 09 | 54046 | 2.90 | 2.80 | 70 | 9 | yes | 2.0 - 3.0 | -20 / +80 | Chrome leather, grey, ground | Polyamide fabric, black | Polyamide foil |
| LT 12 | 54047 | 3.20 | 3.20 | 100 | 12 | yes | 2.0 - 3.0 | -20 / +80 | Chrome leather, grey, ground | Polyamide fabric, black | Polyamide foil |
| LT 15 | 54048 | 3.60 | 3.70 | 150 | 15 | yes | 2.0 - 3.0 | -20 / +80 | Chrome leather, grey, ground | Polyamide fabric, black | Polyamide foil |
| LT 18 | 54049 | 3.90 | 4.40 | 200 | 18 | yes | 2.0 - 3.0 | -20 / +80 | Chrome leather, grey, ground | Polyamide fabric, black | Polyamide foil |
| LT 27 | 54050 | 4.80 | 5.60 | 350 | 27 | yes | 2.0 - 3.0 | -20 / +80 | Chrome leather, grey, ground | Polyamide fabric, black | Polyamide foil |
| LT 36 | 54051 | 5.90 | 6.60 | 400 | 36 | yes | 2.0 - 3.0 | -20 / +80 | Chrome leather, grey, ground | Polyamide fabric, black | Polyamide foil |
| LL 06 | 54038 | 3.80 | 3.70 | 70 | 6 | yes | 2.0 - 3.0 | -20 / +80 | Chrome leather, grey, ground | Chrome leather, grey, ground | Polyamide foil |
| LL 09 | 54039 | 4.20 | 4.00 | 90 | 9 | yes | 2.0 - 3.0 | -20 / +80 | Chrome leather, grey, ground | Chrome leather, grey, ground | Polyamide foil |
| LL 12 | 54040 | 4.50 | 4.60 | 120 | 12 | yes | 2.0 - 3.0 | -20 / +80 | Chrome leather, grey, ground | Chrome leather, grey, ground | Polyamide foil |
| LL 18 | 54042 | 5.20 | 6.20 | 200 | 18 | yes | 2.0 - 3.0 | -20 / +80 | Chrome leather, grey, ground | Chrome leather, grey, ground | Polyamide foil |

RAPPLON® Classic Flat Belts

| Belt type | Article Number | Belt thickness [mm] | Belt weight [kg/m ²] | Min. pulley diameter [mm, 20°C] | Belt factor at 1% elongation [N/mm] | Antistatic [AS] | Recommended elongation [%] | Thermal application range [°C] | Cover running side [Material, colour, surface structure] | Cover back side [Material, colour, surface structure] | Tension member [Material] |
|-------------------------------------------------|----------------|---------------------|----------------------------------|---------------------------------|-------------------------------------|-----------------|----------------------------|--------------------------------|----------------------------------------------------------|-------------------------------------------------------|---------------------------|
| Tangential drive belts | | | | | | | | | | | |
| GG 04.16 RF | 54252 | 1.70 | 1.90 | 20 | 4 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, green, rough | XNBR elastomer, blue, fine | Polyamide foil |
| GG 06.18 RF | 54253 | 1.90 | 2.00 | 40 | 6 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, green, rough | XNBR elastomer, blue, fine | Polyamide foil |
| GG 09.24 RF | 54254 | 2.20 | 2.50 | 60 | 9 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, green, rough | XNBR elastomer, blue, fine | Polyamide foil |
| GG 11.25 RR | 54295 | 2.50 | 2.80 | 60 | 11 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, green, rough | XNBR elastomer, blue, rough | Polyamide foil |
| GG 12.30 RR | 54256 | 2.80 | 3.10 | 80 | 12 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, blue, rough | XNBR elastomer, blue, rough | Polyamide foil |
| GG 15.30 RR | 54257 | 3.10 | 3.50 | 100 | 15 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, blue, rough | XNBR elastomer, blue, rough | Polyamide foil |
| GG 15.40 RR | 54277 | 4.00 | 4.60 | 100 | 15 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, blue, rough | XNBR elastomer, blue, rough | Polyamide foil |
| GG 18.33 RR | 54258 | 3.40 | 3.90 | 150 | 18 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, blue, rough | XNBR elastomer, blue, rough | Polyamide foil |
| GG 18.40 RR | 54259 | 3.90 | 4.40 | 160 | 18 | yes | 2.0 - 3.0 | -20 / +100 | XNBR elastomer, blue, rough | XNBR elastomer, blue, rough | Polyamide foil |
| Spindle tapes | | | | | | | | | | | |
| EC-Tape | 545480 | 0.55 | 0.56 | 10 | 1.9 | yes | 0.3 - 2.1 | -20 / +100 | Mixed fabric, white | NBR elastomer, green, smooth | Mixed fabric |
| SSB 84 | 54055 | 0.70 | 0.65 | 20 | 2 | yes | 0.3 - 2.1 | -20 / +100 | Mixed fabric, white | NBR elastomer, blue, fine | Polyamide foil |
| Drive belts with grooved elastomer cover | | | | | | | | | | | |
| GR 09 | 54291 | 3.00 | 3.10 | 60 | 9 | yes | 2.0 - 3.0 | -20 / +100 | NBR elastomer, black, grooved | NBR elastomer, green, rough | Polyamide foil |
| GR 12 | 54292 | 3.40 | 3.60 | 80 | 12 | yes | 2.0 - 3.0 | -20 / +100 | NBR elastomer, black, grooved | NBR elastomer, green, rough | Polyamide foil |
| GR 22 | 54297 | 4.60 | 4.90 | 220 | 22 | yes | 2.0 - 3.0 | -20 / +100 | NBR elastomer, black, grooved | NBR elastomer, green, rough | Polyamide foil |
| GR 33 | 54298 | 5.70 | 6.20 | 310 | 33 | yes | 2.0 - 3.0 | -20 / +100 | NBR elastomer, black, grooved | NBR elastomer, green, rough | Polyamide foil |

Your global contact

International Head Office:

Ammeraal Beltech Holding B.V.
Handelsstraat 1
P.O. Box 38
1700 AA Heerhugowaard
The Netherlands

T +31 72 5751212
F +31 72 5716455
info@ammeraalbeltech.com
www.ammeraalbeltech.com

Austria

T +43 1 2929372
F +43 1 2928906
info@ammeraalbeltech.at

Belgium

T +32 2 466 0300
F +32 2 466 4272
salesgb@ammeraal-beltech.be

Brazil

T +55 11 4655 1244
F +55 11 4655 10 99
vendas@ammeraalbeltech.com.br

Canada

T +1 905 890 1311
F +1 905 890 3660
info@ammeraalbeltech.ca

Chile

T +56 266 96975
F +56 266 96709
info@ammeraalbeltech.cl

China

T +86 21 6534 4690
F +86 21 6548 0430
webmaster@ammeraalbeltech.com.cn

Czech Republic

T +420 56 7330 056
F +420 56 7330 637
prodej@ammeraalbeltech.cz

Finland

T +358 3 278 4400
F +358 3 273 1400
info@ammeraalbeltech.fi

France

T +33 3 20 90 36 00
F +33 3 20 32 29 17
client@ammeraalbeltech.fr

Germany

T +49 4152 937-0
F +49 4152 77695
sales@ammeraal-beltech.de

Hungary

T +36 234 275 10
F +36 234 275 11
info@ammeraalbeltech.hu

Italy

T +39 051 660 60 06
F +39 051 660 60 16
info@ammeraalbeltech.it

Luxembourg

T +352 26 48 38 56
F +352 26 48 38 57
sales@ammeraal-beltech.lu

Malaysia

T +60 3 806 188 49
F +60 3 806 189 35
sales.kl@ammeraalbeltech.com.my

Netherlands

T +31 72 57 51212
F +31 72 57 43364
info@ammeraalbeltech.nl

Portugal

T +351 22 947 94 40
F +351 22 941 30 81
geral@ammeraalbeltech.pt

Singapore

T +65 62739767
F +65 62735490
sales@ammeraalbeltech.com.sg

Slovakia

T +421 2 55648541-2
F +421 2 55648543
predaj@ammeraalbeltech.sk

South Korea

T +82 31 448 3613-7
F +82 31 448 3618
amel@ammeraalbeltech.co.kr

Spain

T +34 93 718 3305
F +34 93 718 6273
ventas@ammeraalbeltech.es

Sweden

T +46 44 43015
F +46 44 43349
info@ammeraal-beltech.se

Switzerland

T +41 55 2253 535
F +41 55 2253 636
verkauf.schweiz@ammeraal-beltech.ch

Thailand

T +66 2 902 2604-13
F +66 2 902 0422
sales@ammeraalbeltech.th.com

United Kingdom

T +44 1992 500550
F +44 1992 553010
sales@ammeraalbeltech.co.uk

United States

T +1 847 673 6720
F +1 847 673 6373
info@ammeraalbeltechusa.com