



Mounting Distances

Min - 618.0mm[24.33in]
 Max - 668.8mm[26.33in]

Electrical

IP69k - Junction Box, Conduit Threads: 1/2" NPT
 24N/28P, G3.0.9.52

Face

Cut into Shell, Volta SuperDrive, 13 Teeth, 164.3mm OD

IP Rating

IP69k

PART NO. OD69-120-135-610-11403

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN mm TOLERANCES: 0-6: ±0.1 >6-30: ±0.2 >30-120: ±0.3 >120-400: ±0.4 >400-1000: ±0.5	DRAWN	GB	08/25/22
	CHECKED	CD	08/25/22
	ENG APPR.		
MATERIAL	SS 316		
FINISH	N/A		
DO NOT SCALE DRAWING			

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ONE MOTION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ONE MOTION IS PROHIBITED.

TITLE:
 Powered Pulley, IP69k, 120Nm (88.6 ft/lbs), Dual Core: 480mm (18.9"), 24N/28P, G3.0.9.52, 135mm (5.3"), 610mm (24"), Volta SuperDrive Cut shell, IP69k-Junction Box, Conduit Threads: 1/2 NPT, Four Flats(20mm), Flat Width: 25.4mm (1"), Mounting: Offsets- 4mm (0.16") | Min- 618mm (24.3") / Max- 668.8mm (26.3")

SIZE A		REV 00
SCALE: 1:5	Weight(kg): 83.56	SHEET 1 OF 1