



Mounting Distances

Min - 313.0mm [12.32in]
 Max - 363.8mm [14.32in]

Electrical

IP69k-Junction Box
 36N/40P, G3.1.2.55

Face

Cut Into Shell, Volta SuperDrive, 19 Teeth, 241.5mm [9.51in] OD

IP Rating

IP69k

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN mm

TOLERANCES:

0-6: ±0.1
 >6-30: ±0.2
 >30-120: ±0.3
 >120-400: ±0.4
 >400-1000: ±0.5

MATERIAL

SS 316

FINISH

N/A

DO NOT SCALE DRAWING

	NAME	DATE
DRAWN	HS	12/27/21
CHECKED	CD	12/27/21
ENG APPR.		

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ONE MOTION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ONE MOTION IS PROHIBITED.

PART NO. OD69-180-215-305-11868

TITLE: Powered Pulley, IP69k, 180Nm (132.8 ft/lbs), Single Core: 150mm (5.91"), 36N/40P, G3.1.2.55, 215mm (8.5"), 305mm (12"), Volta SuperDrive, IP69k-Junction Box, Four Flats(20mm), Flat Width: 25.4mm (1"), Mounting: Offsets-4mm (0.16") | Min-313mm (12.3") / Max-363.8mm (14.3")

SIZE A	ONE MOTION	REV 00
SCALE: 1:5	Weight(kg): 69.57	SHEET 1 OF 1