

## RAPPLON® Flat Belts Sales Program 2012



### RAPPLON® QuickSplice Flat belts

- Process belts
- Elastic process belts
- Drive belts and Tangential drive belts

### RAPPLON® Classic Flat belts

- Process belts
- Drive belts with elastomer cover
- Drive belts with leather cover
- Tangential drive belts
- Spindle tapes
- Drive belts with grooved elastomer cover

# RAPPLON® QuickSplice Flat Belts

Belt type	Article Number	Belt thickness [mm]	Belt weight [kg/m <sup>2</sup> ]	Min. pulley diameter [mm, 20°C]	Belt factor at 1% elongation [N/mm]	Antistatic [AS]	Recommended elongation [%]	Thermal application range [°C]	Cover running side [Material, colour, surface structure]	Cover back side [Material, colour, surface structure]	Tension member [Material]
<b>Process belts</b>											
<b>TT E05.11 Q</b>	54599	1.10	1.10	25	5	yes	0.5 - 2.1	+0 / +60	Polyester fabric, grey	Polyester fabric, black	Polyester fabric
<b>TT E09.18 Q</b>	54598	1.85	1.90	25	9	yes	0.5 - 2.1	+0 / +60	Mixed fabric, grey	Mixed fabric, grey	Polyester fabric
<b>TT P02.12 Q</b>	54601	1.20	1.00	10	2	yes	1.0 - 2.0	+0 / +60	Polyamide fabric, green	Polyamide fabric, black	Polyamide fabric
<b>PG E05.12 SFQ</b>	54630	1.20	1.20	20	5	yes	0.5 - 2.0	+0 / +60	Thermoplastic elastomer, black, fine	XNBR elastomer, green, fine	Polyester fabric
<b>PG E08.18 SFQ</b>	54631	1.85	1.90	30	8	yes	0.5 - 2.0	+0 / +60	Thermoplastic elastomer, black, fine	XNBR elastomer, green, fine	Polyester fabric
<b>TG E04.12 RQ</b>	54624	1.25	1.25	15	4	yes	0.5 - 2.0	+0 / +60	Polyester fabric, green	XNBR elastomer, green, rough	Polyester fabric
<b>TU E04.09 RQ</b>	54603	0.90	1.05	15	4	yes	0.5 - 2.0	+0 / +60	Polyester fabric	Polyurethane, black, rough	Polyester fabric
<b>GG E03.14 FFQ</b>	54583	1.40	1.45	20	3.1	yes	0.5 - 2.0	+0 / +60	XNBR elastomer, grey, fine	XNBR elastomer, grey, fine	Polyester fabric
<b>GG E05.14 FFQ</b>	54607	1.40	1.50	25	5	yes	0.5 - 2.0	+0 / +60	XNBR elastomer, black, fine	XNBR elastomer, green, fine	Polyester fabric
<b>GG E10.30 RRQ</b>	54636	3.00	3.10	30	10	yes	0.5 - 1.0	+0 / +60	XNBR elastomer, blue, rough	XNBR elastomer, blue, rough	Polyester fabric
<b>GG E10.40 RRQ</b>	54637	4.00	4.20	40	10	yes	0.5 - 1.0	+0 / +60	XNBR elastomer, blue, rough	XNBR elastomer, blue, rough	Polyester fabric
<b>GG E10.55 RRQ</b>	54638	5.50	6.10	60	10	yes	0.5 - 1.0	+0 / +60	XNBR elastomer, blue, rough	XNBR elastomer, blue, rough	Polyester fabric
<b>GG P01.14 FFQ</b>	54582	1.40	1.40	15	1	yes	0.5 - 2.0	+0 / +60	XNBR elastomer, green, fine	XNBR elastomer, green, fine	Polyamide fabric
<b>Drive belts and Tangential drive belts</b>											
<b>GG E08.20 RRQ</b>	54614	2.00	2.00	25	8	yes	0.5 - 2.0	+0 / +60	XNBR elastomer, black, rough	XNBR elastomer, blue, rough	Polyester fabric
<b>GG E15.20 RRQ</b>	54626	2.00	2.20	25	15	yes	0.5 - 2.0	+0 / +60	XNBR elastomer, green, rough	XNBR elastomer, blue, rough	Polyester fabric
<b>GG E15.25 RRQ</b>	54618	2.50	2.50	30	15	yes	0.5 - 2.0	+0 / +60	XNBR elastomer, green, rough	XNBR elastomer, blue, rough	Polyester fabric
<b>GG E15.30 RRQ</b>	54609	3.00	3.30	30	15	yes	0.5 - 2.0	+0 / +60	XNBR elastomer, green, rough	XNBR elastomer, blue, rough	Polyester fabric
<b>GG E35.30 RRQ</b>	54627	3.00	3.40	60	35	yes	0.5 - 2.0	+0 / +60	XNBR elastomer, black, rough	XNBR elastomer, blue, rough	Polyester fabric
<b>UU E15.30 RRQ</b>	54538	3.00	3.30	30	15	yes	0.5 - 2.0	+0 / +60	Polyurethane, green, rough	Polyurethane, green, rough	Polyester fabric

# RAPPLON® QuickSplice Flat Belts


Belt type	Article Number	Belt thickness [mm]	Belt weight [kg/m <sup>2</sup> ]	Min. pulley diameter [mm, 20°C]	Belt factor at 6% elongation [N/mm]	Antistatic [AS]	Recommended elongation [%]	Thermal application range [°C]	Cover running side [Material, colour, surface structure]	Cover back side [Material, colour, surface structure]	Tension member [Material]
<b>Elastic process belts</b>											
<b>GG N08 RRQ</b>	54262	1.60	1.40	15	0.8	yes	4.0 - 8.0	+0 / +60	XNBR elastomer, black, rough	XNBR elastomer, green, rough	Thermoplastic elastomer
<b>GG N15 FFQ</b>	54585	1.40	1.40	15	1.5	yes	4.0 - 8.0	+0 / +60	XNBR elastomer, black, fine	XNBR elastomer, black, fine	Thermoplastic elastomer
<b>GG N22 RFQ</b>	54263	1.50	1.40	15	2.2	yes	4.0 - 8.0	+0 / +60	XNBR elastomer, black, rough	XNBR elastomer, green, fine	Thermoplastic elastomer
<b>GG N27 RFQ</b>	54608	1.70	1.65	15	2.7	yes	4.0 - 8.0	+0 / +60	XNBR elastomer, black, rough	XNBR elastomer, blue, fine	Thermoplastic elastomer
<b>GV N20.17 RQ</b>	54547	1.70	1.50	15	2.0	yes	0.5 - 2.0	+0 / +60	XNBR elastomer, black, rough	Fleece, ground quality, grey	Thermoplastic elastomer
<b>UU N05 RFQ</b>	54544	0.80	0.95	20	0.5	yes	3.0 - 6.0	+0 / +60	Polyurethane, black, rough	Polyurethane, blue, fine	Polyurethane
<b>UU N06 RFQ</b>	54545	1.10	1.20	20	0.6	yes	3.0 - 6.0	+0 / +60	Polyurethane, black, rough	Polyurethane, blue, fine	Polyurethane
<b>UU N08 RSQ</b>	54540	1.10	1.30	20	0.8	yes	3.0 - 6.0	+0 / +60	Polyurethane, rough, black	Polyurethane, smooth, royal blue	Polyurethane
<b>UU N08 RSQ FG</b>	54543	0.80	0.95	6	0.8	no	3.0 - 6.0	+0 / +60	Polyurethane, white, rough	Polyurethane, white, smooth	Polyurethane
<b>UV N12 FQ</b>	54557	1.50	1.70	20	1.2	yes	0.5 - 2.0	+0 / +60	Polyurethane, blue, fine	Fleece, ground quality, grey	Polyurethane

# RAPPLON® QuickSplice Tools


## Finger cutting equipment




HFT 30/100 & HFT 50/100



HFT 120



MFT 60/MFT 130/MFT 250



MFT 400

## Heating pliers



QSP 60 plus



QSP 60LF plus



QSP 105 plus



QSP 160 plus

# RAPPLON® Classic Flat Belts

Belt type	Article Number	Belt thickness [mm]	Belt weight [kg/m <sup>2</sup> ]	Min. pulley diameter [mm, 20°C]	Belt factor at 1% elongation [N/mm]	Antistatic [AS]	Recommended elongation [%]	Thermal application range [°C]	Cover running side [Material, colour, surface structure]	Cover back side [Material, colour, surface structure]	Tension member [Material]
<b>Process belts</b>											
<b>S09 C</b>	54504	0.90	1.00	60	9	yes	2.0 - 3.0	+0 / +80	Polyamide foil, transp., smooth	Polyamide foil, transp., smooth	Polyamide foil
<b>TT S02.10 C</b>	54270	1.00	0.85	10	2	yes	2.0 - 3.0	+0 / +80	Polyamide fabric, blue	Polyamide fabric, blue	Polyamide foil
<b>TT S04.12 C</b>	54054	1.20	1.15	20	4	yes	2.0 - 3.0	+0 / +80	Polyamide fabric, blue	Polyamide fabric, blue	Polyamide foil
<b>TT S04.12 C black</b>	54251	1.20	1.10	20	4	yes	2.0 - 3.0	+0 / +80	Polyamide fabric, black	Polyamide fabric, black	Polyamide foil
<b>TT S09.16 C black</b>	54250	1.65	1.65	60	9	yes	2.0 - 3.0	+0 / +80	Polyamide fabric, black	Polyamide fabric, black	Polyamide foil
<b>GG S02 FFC</b>	54264	1.50	1.65	10	2	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, blue, fine	XNBR elastomer, blue, fine	Polyamide foil
<b>GG S02 RRC</b>	54009	1.10	1.20	10	2	yes	2.0 - 3.0	+0 / +80	NBR elastomer, blue, rough	NBR elastomer, blue, rough	Polyamide foil
<b>GG S04 RRC</b>	54010	1.30	1.50	20	4	yes	2.0 - 3.0	+0 / +80	NBR elastomer, blue, rough	NBR elastomer, blue, rough	Polyamide foil
<b>GG S06.30 RRC</b>	54274	3.00	3.30	30	6	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, green, rough	XNBR elastomer, green, rough	Polyamide foil
<b>GG S06.40 RRC</b>	54145	4.00	4.40	40	6	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, green, rough	XNBR elastomer, green, rough	Polyamide foil
<b>GG S06.50 RRC</b>	54275	5.00	5.50	50	6	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, green, rough	XNBR elastomer, green, rough	Polyamide foil
<b>GG S06.60 RRC</b>	54276	6.00	6.80	60	6	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, green, rough	XNBR elastomer, green, rough	Polyamide foil
<b>GG S07.30 RRC</b>	54243	3.00	3.40	40	7	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, blue, rough	XNBR elastomer, blue, rough	Polyamide foil
<b>GG S09.31 RRC</b>	54133	3.10	3.50	80	9	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, blue, rough	XNBR elastomer, blue, rough	Polyamide foil
<b>GG S11.50 RRC</b>	54278	5.00	5.70	60	11	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, blue, rough	XNBR elastomer, blue, rough	Polyamide foil

# RAPPLON® Classic Flat Belts

Belt type	Article Number	Belt thickness [mm]	Belt weight [kg/m <sup>2</sup> ]	Min. pulley diameter [mm, 20°C]	Belt factor at 1% elongation [N/mm]	Antistatic [AS]	Recommended elongation [%]	Thermal application range [°C]	Cover running side [Material, colour, surface structure]	Cover back side [Material, colour, surface structure]	Tension member [Material]
<b>Process belts</b>											
<b>TG E10.17 SC</b>	55145	1.70	1.90	60	10	no	0.2 - 0.6	-0 / +80	Polyester fabric, natural	NBR elastomer, white, smooth	Polyester fabric
<b>TG E10.19 P5C</b>	55141	1.90	1.90	60	10	no	0.2 - 0.6	-0 / +80	Polyester fabric, natural	NBR elastomer, white, P5	Polyester fabric
<b>TG E12.65 FC</b>	56420	6.50	6.80	80	12	yes	0.2 - 0.6	-0 / +80	Polyester fabric, black	Natural rubber, red, smooth	Polyester fabric
<b>TG E18.20 P5C</b>	57239	2.00	1.80	60	18	yes	0.2 - 0.6	-0 / +80	Polyester fabric, natural	NBR elastomer, green, P5	Polyester fabric
<b>TG P03.12 FC</b>	54525	1.25	1.20	25	3	yes	0.2 - 0.6	-0 / +80	Polyamide fabric, black	XNBR elastomer, green, fine	Polyamide fabric
<b>TG P04.20 RC</b>	54265	2.00	2.00	25	3.8	yes	0.2 - 0.6	-0 / +80	Polyamide fabric, black	NBR elastomer, green, rough	Polyamide fabric
<b>TG P07.29 RC</b>	54266	2.90	3.00	50	7	yes	0.2 - 0.6	-0 / +80	Polyamide fabric, black	NBR elastomer, green, rough	Polyamide fabric
<b>TG P07.41 RC</b>	54267	4.10	4.30	60	7	yes	0.2 - 0.6	-0 / +80	Polyamide fabric, black	NBR elastomer, green, rough	Polyamide fabric
<b>TG P07.60 RC</b>	54268	6.00	6.50	100	7	yes	0.2 - 0.6	-0 / +80	Polyamide fabric, black	NBR elastomer, green, rough	Polyamide fabric
<b>TG S04.14 RC</b>	54261	1.40	1.40	20	4	yes	2.0 - 3.0	-0 / +80	Polyamide fabric, green	XNBR elastomer, green, rough	Polyamide foil
<b>TG S04.12 RC</b>	54269	1.25	1.25	20	4	yes	2.0 - 3.0	-0 / +80	Polyamide fabric, green	NBR elastomer, green, coarse	Polyamide foil
<b>TG S06.27 RC</b>	54034	2.70	3.10	50	6	yes	2.0 - 3.0	-0 / +80	Polyamide fabric, blue	NBR elastomer, blue, rough	Polyamide foil
<b>TG S09.58 RC</b>	54036	5.80	6.80	80	9	yes	2.0 - 3.0	-0 / +80	Polyamide fabric, blue	NBR elastomer, blue, rough	Polyamide foil

## Surface structure P5

P5 > Fabric structure



# RAPPLON® Classic Flat Belts

Belt type	Article Number	Belt thickness [mm]	Belt weight [kg/m <sup>2</sup> ]	Min. pulley diameter [mm, 20°C]	Belt factor at 1% elongation [N/mm]	Antistatic [AS]	Recommended elongation [%]	Thermal application range [°C]	Cover running side [Material, colour, surface structure]	Cover back side [Material, colour, surface structure]	Tension member [Material]
<b>Drive belts with elastomer cover</b>											
GT S02 RC	54001	1.10	1.00	10	2	yes	2.0 - 3.0	+0 / +80	NBR elastomer, blue, rough	Polyamide fabric, blue	Polyamide foil
GT S04 RC	54002	1.30	1.30	20	4	yes	2.0 - 3.0	+0 / +80	NBR elastomer, blue, rough	Polyamide fabric, blue	Polyamide foil
GT S06 RC	54003	1.40	1.50	40	6	yes	2.0 - 3.0	+0 / +80	NBR elastomer, blue, rough	Polyamide fabric, blue	Polyamide foil
GT S09 FC	54166	1.90	2.10	40	9	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, blue, fine	Polyamide fabric, blue	Polyamide foil
GG S06.20 RRC	54100	2.00	2.20	40	6	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, blue, rough	XNBR elastomer, blue, rough	Polyamide foil
GG S09.23 RRC	54098	2.30	2.50	60	9	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, blue, rough	XNBR elastomer, blue, rough	Polyamide foil
<b>Drive belts with leather cover</b>											
LT S06 C	54045	2.60	2.50	50	6	yes	2.0 - 3.0	+0 / +80	Chrome leather, grey, ground	Polyamide fabric, black	Polyamide foil
LT S09 C	54046	2.90	2.80	70	9	yes	2.0 - 3.0	+0 / +80	Chrome leather, grey, ground	Polyamide fabric, black	Polyamide foil
LT S11 C	54047	3.00	3.00	100	11	yes	2.0 - 3.0	+0 / +80	Chrome leather, grey, ground	Polyamide fabric, black	Polyamide foil
LT S15 C	54048	3.60	3.70	150	15	yes	2.0 - 3.0	+0 / +80	Chrome leather, grey, ground	Polyamide fabric, black	Polyamide foil
LT S18 C	54049	3.90	4.40	200	18	yes	2.0 - 3.0	+0 / +80	Chrome leather, grey, ground	Polyamide fabric, black	Polyamide foil
LT S27 C	54050	4.80	5.60	350	27	yes	2.0 - 3.0	+0 / +80	Chrome leather, grey, ground	Polyamide fabric, black	Polyamide foil
LT S36 C	54051	5.90	6.60	400	36	yes	2.0 - 3.0	+0 / +80	Chrome leather, grey, ground	Polyamide fabric, black	Polyamide foil
LL S06 C	54038	3.80	3.70	70	6	yes	2.0 - 3.0	+0 / +80	Chrome leather, grey, ground	Chrome leather, grey, ground	Polyamide foil
LL S09 C	54039	4.20	4.00	90	9	yes	2.0 - 3.0	+0 / +80	Chrome leather, grey, ground	Chrome leather, grey, ground	Polyamide foil
LL S11 C	54040	4.50	4.60	120	11	yes	2.0 - 3.0	+0 / +80	Chrome leather, grey, ground	Chrome leather, grey, ground	Polyamide foil
LL S18 C	54042	5.20	6.20	200	18	yes	2.0 - 3.0	+0 / +80	Chrome leather, grey, ground	Chrome leather, grey, ground	Polyamide foil

# RAPPLON® Classic Flat Belts

Belt type	Article Number	Belt thickness [mm]	Belt weight [kg/m <sup>2</sup> ]	Min. pulley diameter [mm, 20°C]	Belt factor at 1% elongation [N/mm]	Antistatic [AS]	Recommended elongation [%]	Thermal application range [°C]	Cover running side [Material, colour, surface structure]	Cover back side [Material, colour, surface structure]	Tension member [Material]
<b>Tangential drive belts</b>											
<b>GG S04.17 RFC</b>	54252	1.70	1.90	20	4	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, green, rough	XNBR elastomer, blue, fine	Polyamide foil
<b>GG S06.19 RFC</b>	54253	1.90	1.90	40	6	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, green, rough	XNBR elastomer, blue, fine	Polyamide foil
<b>GG S09.22 RFC</b>	54254	2.20	2.50	60	9	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, green, rough	XNBR elastomer, blue, fine	Polyamide foil
<b>GG S11.25 RRC</b>	54295	2.50	2.80	60	11	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, green, rough	XNBR elastomer, blue, rough	Polyamide foil
<b>GG S11.25 RFC</b>	54296	2.50	2.80	60	11	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, green, rough	XNBR elastomer, blue, fine	Polyamide foil
<b>GG S11.28 RRC</b>	54256	2.80	3.10	80	11	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, blue, rough	XNBR elastomer, blue, rough	Polyamide foil
<b>GG S15.31 RRC</b>	54257	3.10	3.10	80	15	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, blue, rough	XNBR elastomer, blue, rough	Polyamide foil
<b>GG S15.40 RRC</b>	54277	4.00	4.60	100	15	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, blue, rough	XNBR elastomer, blue, rough	Polyamide foil
<b>GG S18.34 RRC</b>	54258	3.40	3.90	150	18	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, blue, rough	XNBR elastomer, blue, rough	Polyamide foil
<b>GG S18.39 RRC</b>	54259	3.90	4.40	160	18	yes	2.0 - 3.0	+0 / +80	XNBR elastomer, blue, rough	XNBR elastomer, blue, rough	Polyamide foil
<b>Spindle tapes</b>											
<b>GT P2.05 SC</b>	545480	0.55	0.60	10	1.9	yes	0.5 - 2.0	+0 / +80	Mixed fabric, white	NBR elastomer, green, smooth	Mixed fabric
<b>GT S02.07 FC</b>	54055	0.70	0.65	20	2	yes	0.5 - 2.0	+0 / +80	Mixed fabric, white	NBR elastomer, blue, fine	Polyamide foil
<b>Drive belts with grooved elastomer cover</b>											
<b>GG S11 LRC</b>	54289	3.25	3.60	80	11	yes	2.0 - 3.0	+0 / +80	NBR elastomer, black, grooved	NBR elastomer, green, rough	Polyamide foil
<b>GG S22 LRC</b>	54297	4.60	4.90	220	22	yes	2.0 - 3.0	+0 / +80	NBR elastomer, black, grooved	NBR elastomer, green, rough	Polyamide foil
<b>GG S33 LRC</b>	54298	5.70	6.20	310	33	yes	2.0 - 3.0	+0 / +80	NBR elastomer, black, grooved	NBR elastomer, green, rough	Polyamide foil

# Your global contact

International Head Office:

**Ammeraal Beltech** Holding B.V.  
Handelsstraat 1  
P.O. Box 38  
1700 AA Heerhugowaard  
The Netherlands

T +31 72 5751212  
F +31 72 5716455  
info@ammeraalbeltech.com  
www.ammeraalbeltech.com

## Austria

T +43 171728 133  
F +43 171728 110  
info@ammeraalbeltech.at

## Belgium

T +32 2 466 0300  
F +32 2 466 4272  
salesgb@ammeraal-beltech.be

## Canada

T +1 905 890 1311  
F +1 905 890 3660  
info@ammeraalbeltech.ca

## Chile

T +56 266 96975  
F +56 266 96709  
info@ammeraalbeltech.cl

## China

T +86 21 6534 4690  
F +86 21 6548 0430  
webmaster@ammeraalbeltech.com.cn

## Czech Republic

T +420 567 117 211  
F +420 567 117 208  
prodej@ammeraalbeltech.cz

## Denmark

T +45 7572 3100  
F +45 7572 3148  
admينة@unichains.dk

## Finland

T +358 207 911400  
F +358 207 911450  
info@ammeraalbeltech.fi

## France

T +33 3 20 90 36 00  
F +33 3 20 32 29 17  
client@ammeraalbeltech.fr

## Germany

T +49 4152 937-0  
F +49 4152 77695  
sales@ammeraal-beltech.de

## Hungary

T +36 234 275 10  
F +36 234 275 11  
info@ammeraalbeltech.hu

## India

T +91 44 265 34 244  
info@ammeraalbeltech.net.in  
www.ammeraalbeltech.com

## Italy

T +39 051 660 60 06  
F +39 051 660 60 16  
info@ammeraalbeltech.it

## Luxembourg

T +352 26 48 38 56  
F +352 26 48 38 57  
sales@ammeraal-beltech.lu

## Malaysia

T +60 3 806 188 49  
F +60 3 806 189 35  
sales.kl@ammeraalbeltech.com.my

## Netherlands

T +31 72 57 51212  
F +31 72 57 43364  
info@ammeraalbeltech.nl

## Poland

T +48 32 44 77 179  
biuro@ammeraal-beltech.pl  
www.ammeraal-beltech.pl

## Portugal

T +351 22 947 94 40  
F +351 22 941 30 81  
geral@ammeraalbeltech.pt

## Singapore

T +65 62739767  
F +65 62735490  
sales@ammeraalbeltech.com.sg

## Slovakia

T +421 2 55648541-2  
F +421 2 55648543  
predaj@ammeraalbeltech.sk

## South Korea

T +82 31 448 3613-7  
F +82 31 448 3618  
amel@ammeraalbeltech.co.kr

## Spain

T +34 93 718 3054  
F +34 93 718 3843  
ventas@ammeraalbeltech.es

## Sweden

T +46 44 7803010  
F +46 44 43349  
info@ammeraal-beltech.se

## Switzerland

T +41 55 2253 535  
F +41 55 2253 636  
info@ammeraal-beltech.ch

## Thailand

T +66 2 902 2604-13  
F +66 2 902 0422  
sales@ammeraalbeltech.th.com

## United Kingdom

T +44 1992 500550  
F +44 1992 553010  
sales@ammeraalbeltech.co.uk

## United States

T +1 847 673 6720  
F +1 847 673 6373  
info@ammeraalbeltechusa.com

## Vietnam

T +84 8 376 562 05  
dmh@ammeraalbeltech.com.vn  
www.ammeraalbeltech.com.vn